

MODEL B101



DESCRIPTION


The 16 key plastic keypads is specially designed for public environment applications, such as vending machines, ticket machines, payment terminals, telephones, access controlsystems and industrial machinery.

Keys and front panel are built from engineer plastic with high resistance to impact and vandalism and is also sealed to IP54.


1 MAIN COMPONENTS

- Frame and keys are made of RoHS approved engineer ABS plastic material
- Conductive rubber with carbon granules
 - Contact resistance: $\leq 150\Omega$
 - Elastic force: 200g
- 1.5mm thickness UL approved printed circuit board with golden fingers


2 STRUCTURE DRAWING



3 DIMENSION DRAWING




4 COMMON CIRCUIT




5 SPECIFICATION

Electrical Specification	Power Supply	Nominal 3 VDC
		Max. voltage 12VDC
		Min. voltage 3VDC
	Contact Resistance	≤150Ω
Mechanical Characteristics	Storage Temperature	-40 C ... +85 C
	Operation Temperature	-25 C ... +65 C
	Protection Grade	IP54
	Shock Resistance	IK09
	Electrical Life	1 million cycles of operation per key
	Key Travel	0.45mm
	Actuation Force	250g/2.45N
	Environmental Resistance	Damp heat 21 days +40 C
Saline mist 96 Hours		
Dry heat 10 days +85 C		

6 CONNECTOR




Plug Connector



SCN plug+cable



XH plug+cable




Pins header



DB9 Connector



USB



More

7 APPLICATION

